

Fiber Optic Cable Puller Trailer Specification



TRAILER SPECIFICATIONS

Weight (without puller)	950 lbs (431 kg)
Axle	3,500 lbs (1,590 kg) Type II
Tire	P205/75R14 Steel Belted Radials
Rims	14" x 6" (356 mm x 152 mm)
Track	60" (1,254 mm)
Overall Width	80" (2,032 mm)
Overall Height	51" (1,295 mm)
Hitch	3" (76 mm) Lunette Eye
Lighting	7 Pin Connector
Electronics	12 VDC

POWER SUPPLY

Engine	Briggs & Stratton V-Twin Vanguard OHV gas
Horsepower	16HP @ 3,600 RPM (11.9 kW @3,600 RPM)
Starting	Electric
Fuel	Unleaded Gas, 85 Octane min, 10% or less ethenol blend
Fuel Capacity	5.0 gallons (18.9 liters)
Speed Control	Variable

HYDRAULICS

Capacity	8.2 gpm @ 2,000 psi (31.0 lpm@138 bar)
Reservoir	5.0 gallons (18.9 liters)
Filtration	10 micron return line canister type
Hydraulic Oil Requirements	Petro based, anti-wear, high viscosities over 140
Hydraulic Relief Valve Pressure	2,150 psi (148.3 bar)