

Fiber Optic Cable Puller Specifications



	12 IN (305 MM) DIAMETER CAPSTAN		30 IN (762 MM) DIAMETER CAPSTAN		42 IN (1067 MM) DIAMETER CAPSTAN		50 IN (1270 MM) DIAMETER CAPSTAN	
<i>Pulling Force</i>	<i>lbs</i>	<i>kN</i>	<i>lbs</i>	<i>kN</i>	<i>lbs</i>	<i>kN</i>	<i>lbs</i>	<i>kN</i>
Maximum	2,000	8.9	1,000	4.4	600	2.7	600	2.7
Continuous	2,000	8.9	1,000	4.4	600	2.7	600	2.7
<i>Pulling Speed</i>	<i>ft/min</i>	<i>m/min</i>	<i>ft/min</i>	<i>m/min</i>	<i>ft/min</i>	<i>m/min</i>	<i>ft/min</i>	<i>m/min</i>
No Load	93.9	28.6	240	73.2	328.4	100	391.4	119.3
At Maximum Force	93.9	28.6	240	73.2	328.4	100	391.4	119.3
POWER REQUIREMENTS								
Pressure	2,000 to 2,500 psi (137 to 172 bar)							
Flow	6 to 10 gpm (22.7 to 37.9 lpm)							
Peak Power	8HP (5.97 kw)							